



Triton PS™ Pre-Sloped Shower Board and Shower Components Safety Data Sheet (SDS)

Section 1 – Product and Company Identification

Manufacturer/Distributor: MiTek, Inc

Products: Triton PS™ Pre-Sloped Shower Board, Triton Benches, Niches and Curbs

Address: 770 Bradfield Rd. #575, Houston, TX 77044

Information Phone Number: 833-909-0839

Email: info@tritonwatertight.com

Website: www.tritonwatertight.com

Emergency Phone Number: 877-453-8868

Recommended use: Triton PS™ Pre-Sloped Shower Board and associated foam products are intended for use in place of traditional mud set tile beds and is comprised of two (2) primary components: 1) Triton WP polyethylene and polypropylene waterproofing membrane factory adhered to 2) a pre-sloped expanded polystyrene (EPS) shower board.

Restrictions on use: No known adverse chemical reactions.

Section 2 – Hazard Identification

Triton WP Waterproof Membrane

Route(s) of Entry: Skin (None), Eyes (None), Inhalation (None), Ingestion (None)

Health Hazards (Acute and Chronic):

Skin (No Known Hazard)

Eyes (No Known Hazard)

Inhalation (No Known Hazard)

Ingestion (No Known Hazard)

Carcinogenicity: No Known Toxicity Effects (Skin, Eyes, Inhalation, Ingestion)

Signs and Symptoms of Exposure: Skin (None), Eyes (None), Inhalation (None), Ingestion (None)

Medical Conditions Generally Aggravated by Exposure: None

Pre-Sloped Expanded Polystyrene (EPS) Shower Board

Emergency Overview: Material is flammable and will emit an acrid smoke and potentially toxic fumes when heated to decomposition. Accumulated fine dust may present a risk of explosion in the presence of open flame, sparks, or static electricity discharges.

Route(s) of Entry: Skin (None), Eyes (None), Inhalation (None), Ingestion (None)

Health Hazards (Acute and Chronic):

Skin: Potential mechanical irritation from repetitive handling

Eyes: Potential mechanical irritation from contact with fines

Inhalation: Potential irritation to the respiratory system from inhalation of fines

Ingestion: May be harmful if swallowed, mechanical irritation and blockage of the digestive tract

Carcinogenicity: No Known Toxicity Effects (Skin, Eyes, Inhalation, Ingestion)

Signs and Symptoms of Exposure: Skin (None), Eyes (None), Inhalation (None), Ingestion (None)

Medical Conditions Generally Aggravated by Exposure: None



Section 3 –Composition/ Information on Ingredients

Triton WP Waterproof Membrane

Preparation: Sealing membrane in roll form and preformed components

Chemical Characterization: Polypropylene fleece & polyethylene

Hazard Classification: This material is considered not hazardous by the U.S. Occupational Safety and Health Administration's (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Ingredient Name	CAS Number	Percent of Total Weight
Polypropylene	9003-07-0	~66
Polyethylene	9002-88-4	~34

Pre-Sloped Expanded Polystyrene (EPS) Shower Board

Preparation: Pre-sloped shower board

Chemical Characterization: Expanded polystyrene (EPS)

Hazard Classification: This material is considered not hazardous by the U.S. Occupational Safety and Health Administration's (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Ingredient Name	CAS Number	Percent of Total Weight
Polystyrene	9003-53-6	92-97
n-Pentane	109-66-0	3-8*
Isopentane	78-78-4	0-3*
	*All pentanes (normal- and iso-) combined	3-8

Section 4 – First-aid Measures

Emergency and First Aid Procedures in Case of:

- Contact with skin – remove residue with soap and water, consult a physician in case of skin reaction
- Contact with eyes – flush eyes with water for 10 to 15 minutes while holding eyelids apart, consult an ophthalmologist should symptoms persist
- Inhalation –person affected by formation of dust should be removed to fresh air and kept still, seek medical attention if respiratory difficulties develop
- Ingestion – Not a probable route of exposure; in the case of formation of dust, rinse mouth, seek medical attention if difficulties develop. If ingested, do not induce vomiting, seek immediate medical attention.

Information to Physician – Treat symptomatically

Section 5 – Fire-fighting Measures

See Section 9 Physical and Chemical Properties for flammability limits, flash point, and auto ignition information.

General Fire Hazards: Dangerous fire risk, vigorously supports combustion. When heated to decomposition, product will emit acrid smoke and potentially toxic fumes. Vapors are heavier than air and



may travel along the ground to some distant source of ignition and flash back. Remove additional product from the fire area if safe to do so.

Explosion Hazards: Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back. Accumulated fine dust may form an explosive mixture with air. Prevent contact with electrostatic discharges and other ignition sources. Risk of explosion is increased in the presence of flammable vapors.

Extinguishing Media: Water fog, foam, dry extinguishing powder, carbon dioxide

Specific or Unusual Fire and Explosion Hazards: Flammability characteristics will not be detected by any flash point method

Combustion By-Products: Styrene, oxides of carbon, smoke, carbon black, carbon monoxide, carbon dioxide, and other toxic gasses and decomposition products of hydrocarbons.

Special Fire Fighting Procedures: Do not use direct water stream. Use of foam or water may cause frothing. Apply water from as far away as possible. Do not release runoff from fire control to sewers or waterways. Use water spray to cool exposed products.

Special Protective Equipment: Normal firefighting equipment and thermal protective clothing. Wear self-contained, positive pressure breathing apparatus where smoke is present or may occur.

Fire Fighting Equipment/Instructions: Reference 2008 Emergency Response Guidebook, Guide No. 133 for additional details and instructions. Position upwind and keep unnecessary personnel away. Remove additional product from the fire area if safe to do so. For massive fire, use unmanned holders or monitor nozzles. If not possible, withdraw from area and allow fire to burn. Cool surrounding material with flooding quantities of water until well after fire is extinguished. Control runoff water to prevent entry into sewers, drains, underground or confined spaces, and waterways

Section 6 – Accidental Release Measures

Personnel Precautions: None

Environmental Precautions: Remove

Clean Up Method: Remove mechanically, place in appropriate container for disposal, and dispose in a legal manner consistent with local regulations.

Waste Disposal Method: Remove mechanically, place in appropriate container for disposal, and dispose in a legal manner consistent with local regulations.

Precautions to Be Taken in Handling and Storing: None

Spill and Leak Procedures: Collect and dispose of material in approved container for disposal. If product becomes molten, allow article to cool before disposal or removal from substrate.

Other Precautions: Do not allow waste or residual material to enter into ground water, surface water, or drains.

Section 7 – Handling and Storage

Handling

- Provide adequate ventilation and local exhaust as needed.
- Avoid generation of dust
- Avoid inhalation of dust generated
- Precaution for safe handling – no specific measures
- Personnel precautions – Non hazardous
- Precautions against fire and explosion – slow to ignite, relatively easy to combust

Storage

- Storage conditions – store away from heat sources
- Avoid for storage – Do not freeze



- Incompatible materials – none
- Recommended container – store in original packaging
- Containers not recommended – none

Section 8 – Exposure Controls/ Personal Protection

Skin Protection: None required for recommended use

Eye Protection: Safety glasses

Respiratory Protection: Dust mask as needed

Ventilation: Recommended use requires none in excess of accepted work place safety recommendations

Other Protective Clothing or Equipment: None required for recommended use

Permissible Exposure Limit (PEL): Not applicable for recommended use

Section 9 – Physical and Chemical Properties

Triton WP Waterproof Membrane

Physical Appearance: Solid membrane

Form: 1 meter wide membrane roll, sealing tape roll, and preformed components

Color: Triton yellow

Odor: None

pH Value: No data available

Flash Point: Not applicable

Melting Point: Polypropylene fleece = 160° C; polyethylene foil = 250° C

Initial Boiling Point and Boiling Range: No data available

Evaporation Rate: No data available

Flammability: Combustible

Explosive Properties: Non-explosive

Explosive Limits: Lower Explosion Limit (LEL) – not applicable; Upper Explosion Limit (UEL) – not applicable

Vapor Pressure: No data available

Vapor Density: No data available

Density: 0.95 g/cm³ (specific gravity, water=1)

Water Solubility: Insoluble

Fat Solubility: Almost insoluble

Partition Coefficient: No data available

Auto Ignition Temperature: > 250° C

Thermal Decomposition: No data available

Oxidizing Characteristics: Non-oxidizing

Other Information: Flammable limit > 350° C

Pre-Sloped Expanded Polystyrene (EPS) Shower Board

Physical Appearance: White beads formed into solid

Form: Various dimensions with 2% slope to drain

Color: White

Odor: Slight hydrocarbon

pH Value: Not applicable

Flash Point: -49° C (Pentane)

Melting Point: -129.8° C (Pentane)



Initial Boiling Point and Boiling Range: 36° C (Pentane)
Evaporation Rate: Not applicable
Flammability: Extremely Flammable (Pentane)
Explosive Properties: Non-explosive
Flammability Limits: Lower Flammability Limit (LFL) – 1.4% (Pentane); Upper Flammability Limit (UFL) – 8.3% (Pentane)
Vapor Pressure: 400 mmHg @ 20° C (Pentane)
Vapor Density @ 0° C (air=1): 2.5 (Pentane)
Density: 0.95-1.05 g/cm³ (specific gravity, water=1)
Water Solubility: Insoluble
Solubility: Methanol, methylethylketone, benzene, toluene, or xylene; partially soluble in diethyl ether, n-octanol, acetone
Partition Coefficient: Not applicable
Auto Ignition Temperature: 260° C (Pentane)
Thermal Decomposition: No data available
Oxidizing Characteristics: Non-oxidizing
Other Information: None

Section 10 – Stability and Reactivity

Triton WP Waterproof Membrane

Reactivity: No data Available
Chemical Stability: Stable under recommended usage and storage conditions
Possibility of Hazardous Reactions: No hazardous reaction when material is handled and stored as recommended
Conditions to Avoid: Protect from frost, heat, and sunlight
Incompatible Materials: Strong oxidizing agents and solvents
Hazardous Decomposition Products: If heated to decomposition, product may emit smoke, carbon monoxide, carbon dioxide, and other decomposition products of hydrocarbons
Thermal Decomposition: No data available

Pre-Sloped Expanded Polystyrene (EPS) Shower Board

Chemical Stability: Stable under recommended usage and storage conditions
Chemical Stability – Conditions to Avoid: Keep away from heat and ignition sources. Static electricity discharges, and incompatible materials
Incompatibility: Not resistant to oxidizing agents, dissolves in organic solvents
Hazardous Polymerization: Not expected to occur
Hazardous Decomposition: Styrene, oxides of carbon, and other gasses at elevated temperatures
Special Remarks: Strong oxidizers can increase fire and explosion hazard. Powders or dust may form an explosive mixture with air. Risk of dust-air explosion is increased in the presence of flammable vapors

Section 11 – Toxicological Information

Triton WP Waterproof Membrane

Toxicological Tests

Acute Toxicity (oral): Based on available data, the classification criteria are not met
Acute Toxicity (dermal): Based on available data, the classification criteria are not met
Acute Toxicity (inhalative): Based on available data, the classification criteria are not met
Skin Corrosion/Irritation: Based on available data, the classification criteria are not met
Eye Damage/Irritation: Based on available data, the classification criteria are not met



Respiratory Sensitization: Based on available data, the classification criteria are not met
Skin Sensitization: Based on available data, the classification criteria are not met
Germ Cell Mutagenicity: Based on available data, the classification criteria are not met
Germ Cell Genotoxicity: Based on available data, the classification criteria are not met
Carcinogenicity: Based on available data, the classification criteria are not met
Reproductive Toxicity: Based on available data, the classification criteria are not met
Lactation Effects: Based on available data, the classification criteria are not met
Specific Target Organ Toxicity (single exposure): Based on available data, the classification criteria are not met
Specific Target Organ Toxicity (repeated exposure): Based on available data, the classification criteria are not met
Aspiration Hazard: Based on available data, the classification criteria are not met

Other Information

Polyethylene

- IARC Rating: Group 3
- OSHA Carcinogen: Not listed
- NTP Rating: Not listed

Polyethylene

- IARC Rating: Group 3
- OSHA Carcinogen: Not listed
- NTP Rating: Not listed

Pre-Sloped Expanded Polystyrene (EPS) Shower Board

A: Acute Toxicity – General Product Information

This product has not been tested. Extremely low toxicity risk when used in the intended manner. Exposure to high levels of dusts may be irritating to the eyes. Skin/eye contact with molten or heated may cause burns. Vapors/fumes may be irritating to the respiratory system.

Pentanes, mixed – Contact can irritate the eyes and skin causing a rash and a burning sensation. Inhalation can irritate the nose, throat, and lungs causing coughing, wheezing, and/or shortness of breath.

B: Acute Toxicity – LD50/LC50

n-Pentane (109-66-0)

Inhalation LC50 Rat: 364g/m³/4H; Dermal LD 50 Rabbit: 3000 mg/kg; Oral LD50 Rat: >2000 mg/kg

Isopentane (78-78-4)

Inhalation LC50 Rat: 280000 mg/m³/4H

C: Chronic Toxicity – General Product Information

Pentanes, mixed – Prolonged, repeated skin contact can cause defatting dermatitis with dryness and cracking, redness, and blisters. Chronic pentane exposure may damage the nervous system causing numbness, “pins and needles”, and weakness in the arms and legs.

D: Chronic Toxicity – Carcinogenic Effects

ACGIH, EPA, ISHA, and NTP carcinogen lists have been checked for similar materials or those components with CAS registry numbers

Polystyrene (9003-53-6)

IARC: Supplement 7, 1987; Monograph 19, 1979 (Group 3 (not classifiable))



Section 12 – Ecological Information

Eco Toxicological Effects: No toxicity for the environment. Product is almost completely mechanically separated in water treatment facilities. Do not release or allow to enter into ground water, surface water, or drains. May cause sewer or waterway obstruction and may cause obstruction of digestive tracts of marine life if ingested.

Mobility in Soil: No data available

Persistence and Degradability:

In Soil – Product is not soluble in water and is not biodegradable.

In Water – Product is not soluble in water and is not biodegradable.

Additional Ecological Information: 0% by Weight = 0 g/L

Section 13 – Disposal Considerations

Product – The allocation of waste identity numbers and waste descriptions must be carried out according to the EEC, specific to the industry and process.

Polyethylene – Plastic #4

Polypropylene – Plastic #5

Expanded polystyrene – Not applicable

Contaminated Packaging

Waste Key Number 150101 – Paper and Cardboard Packaging

Waste Key Number 150102 – Plastic Packaging

Section 14 – Transport Information

US Department of Transportation (DOT)/Sea Transport (IMDG)/Air Transport (IATA)

Shipping Name: Polymeric beads, expandable

UN#: 2211

Hazard Class: 9

Packing Group: III

Required Label(s): Class 9: Miscellaneous

Additional Information – US DOT: 2008 Emergency Response Guidebook, Guide No. 133

Additional Information – IMDG: EmS Code: F-A, S-I. Not a marine pollutant

Additional Information – IATA: None

Section 15 – Regulatory Information

US Federal Regulations

Product: TSCA Inventory – not listed

Polyethylene: TSCA Inventory – Listed, EPA Flags XU

TSCA HPVC: not listed

Carcinogen Status:

- IARC Rating: Group 3
- OSHA Carcinogen: Not listed
- NTP Rating: Not listed

Polypropylene: TSCA Inventory – Listed, EPA Flags XU



TSCA HPVC: not listed
 Carcinogen Status:
 - IARC Rating: Group 3
 - OSHA Carcinogen: Not listed
 - NTP Rating: Not listed

EPS:

TSCA Inventory – Listed, EPA Flags XU
 TSCA HPVC: not listed
 Carcinogen Status:
 - IARC Rating: Group 3
 - OSHA Carcinogen: Not listed
 - NTP Rating: Not listed

Section 16 – Other Information

Hazard Rating Systems

NFPA Hazard Rating:

Health: 1 (minimal)
 Fire: 3 (slight)
 Reactivity: 0 (minimal)

HMIS Version III Rating:

Health: 0 (minimal)
 Flammability: 1 (slight)
 Physical Hazard: 0 (minimal)
 Personal Protection: Dust mask, safety glasses



Safety Data Sheet (SDS) issued April 12, 2016

The information contained in this data sheet is furnished in good faith and without warranty, representations, or inducement or license of any kind, except that it is accurate to the best of JetProducts' knowledge, or was obtained from sources believed by JetProducts to be reliable. The accuracy, adequacy or completeness of health and safety precautions set forth herein cannot be guaranteed, and the buyer is solely responsible for ensuring that product is used, handled, stored and disposed of safely and in compliance with applicable federal, state or provincial and local laws. JetProducts disclaims liability for loss, damage or personal injury that arises from, or is in any way related to use of the information contained in this data sheet.